

<u>Technical Data Sheet</u>

# Tartaric acid

# **Product Information**

Product Name: Tartaric acid Catalog Codes: SLT1033, SLT3616, SLT1600 CAS#: 87-69-4 RTECS: WW7875000 TSCA: TSCA 8(b) inventory: L-Tartaric acid CI#: Not available. Synonym: 2,3-Dihydroxybutanedioic acid; L-(+)-Tartaric Acid; Malic acid, 3-hydroxy-; Succinic acid, 2,3-dihydroxy Chemical Name: Tartaric Acid Chemical Formula: HOOC(CHOH)2COOH

## **Physical Properties**

Apperance: colorless translucent crystals or white powder

## Specification

Assay(Titration),  $\% \ge 99.0$ Loss on drying 0.2% Heavy Metal Unit(Pb unit) 0.0001% Max. Specific rotation +12.00° -+12.80° Hefei TNJ Chemical Industry Co.,Ltd.

 B911 Xincheng Business Center,

 Qianshan Rd. Hefei 230022 China

 Tel:
 (0086) 551 65418695

 Fax:
 (0086) 551 65418697

 Email:
 info@tnjchem.com

 Site:
 www.tnjchem.com

## Applications

Tartaric acid is widely used as acidulant in beverage,and other foods, such as soft drinks, wine, candy, bread and some colloidal sweetmeats. With its optical activity, L(+)-Tartaric acid is used as chemical resolving agent to resolve DL-amino-butanol, an intermediate for antitubercular drug. And it is used as chiral pool to synthesize tartarate derivatives. With its acidity, it is used as catalyst in the resin finishing of polyester fabric or pH value regulator in oryzanol production. With its complexation, L(+)-Tartaric acid is used in electroplating, sulfur removal and acid pickling. It is also used as complexing agent, screening agent or chelating agent in chemical analysis and pharmaceutical inspection, or as resist agent in dyeing. With its reduction, it is used as reductive agent in manufacturing mirror chemically or imaging agent in photography. It can also complex with metal ion and can be used as cleaning agent or polishing agent of metal surface.

# Packaging

25kg in fiber drum

# Storage & Handling

Precautions:

Keep container dry. Keep away from heat. Keep away from sources of ignition. Empty containers pose a fire risk, evaporate

the residue under a fume hood. Ground all equipment containing material. Do not breathe dust. Never add water to this

product. Wear suitable protective clothing. In case of insufficient ventilation, wear suitable respiratory equipment. If you

feel unwell, seek medical attention and show the label when possible. Avoid contact with skin and eyes. Keep away from

incompatibles such as oxidizing agents, reducing agents, alkalis.

Storage: Keep container tightly closed. Keep container in a cool, well-ventilated area.

The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchant ability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. In no event shall we be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, howsoever arising, even if we has been advised of the possibility of such damages.

## Hefei TNJ Chemical Industry Co., Ltd.

B911 Xincheng Business Center Qianshan Road, Hefei 230022 Anhui China 

 Tel :
 (0086) 551 5418695

 Fax:
 (0086) 551 5418697

 Email:
 info@tnjchem.com

 Site:
 www.tnjchem.com