

## Hefei TNJ Chemical Industry Co., Ltd.

D1508 Xincheng Business Center, Qianshan Road, Hefei 230022 China Tel : (0086) 551 65418695 Fax: (0086) 551 65418697 Email: info@tnjchem.com Site: www.tnjchem.com

# **Technical Date Sheet**

# **Basic information**

Chemical name	N,N-Dimethylacetamide	Formula	C4H9NO
Synonyms	Acetyldimeethylamine; dimethylacetamid;		°≻-N
	dimethylacetoneamide;		/ \
	Dimethylamide acetate;DMAC		
CAS.No.	127-19-5		
EINECS No.	201-152-2		
Molecular weight	87.12		

## **Physical properties**

Appearance	Colorless liquid	
<b>Density,20℃</b> ,g/cm3	0.942	
Boiling point, $^\circ\!$	166	
Melting point, $^\circ\!$	-20	
Flash point, $^\circ\!$	64	
Refractive index	1.4380	
Solubility	Soluble in water, ethers, esters, ketones and aromatics compounds	

## **Specification**

Items	Industry grade
Appearance	White transparent liquid
Assay, %	≥99.90
Color, Hazan	≦5.0
Water, w/%	≪0.010
lron, w/(mg/kg)	≪0.05
Acidity, w/%	≪0.0030
Basicity,w/%	≪0.00010
Conductivity,us/cm	≪0.05

Application		
Acrylic fibres	Applied as solvent in wet spinning processes for the production of acrylic fibres.	
Elasthane fibres	In the production of polyurethane - based elasthane fibres, is the solvent of choice given its	
	evaporation speed, whether it is used in wet or dry spinning processes.	
Pharm.filed	Used both as a solvent and as a reagent in the production of various pharmaceuticals.	
	In the production of novel x - ray contrast media.	
	Cephalosporins, which are among one of the leading classes of antibiotics, are partly produced from derivatives of 7-ADCA(7-aminodeacetoxy-cephalosporanic acid).	

Various polymers

Used in the manufacturing process. Agood solvent for polyimide resins, both in coating and film production. It is also the ideal solvent for the production of dialyser membranes, based on polysulfones. A mixture of DMAC and lithium chloride is a useful solvent for cellulose fibres in several applications.

## Package

- 190kg/drum, 15.2mt per 20'ft;
- 1mt IBC drum, 20mt per 20'ft;

#### Safety on transportation

It belongs to common goods, always refer to MSDS.

#### Storage and handling

Keep tightyl closed, store in a cool dry place. Please refer to the Materials Safety Data Sheet (MSDS) for the handling methods.

The information above is believed to be accurate and represents the best information currently available to us. However, In no event shall we be liable for any claims, losses, or damages of any third party resulting from its use. *Issue Date*: 1st, 12, 2015