

Hefei TNJ Chemical Industry Co.,Ltd.D1508 Xincheng Business Center,Qianshan Road, Hefei 230022 ChinaTel :(0086) 551 65418678Fax:(0086) 551 65418697Email:info@tnjchem.comSite:www.tnjchem.com

Technical Date Sheet

Basic information

| Chemical name | Diethylene Glycol Monobutyl Ether | Formula | C8H18O3 |
|------------------|--|--------------------|---------|
| Synonyms | Butyl Carbitol / Butyl Diglycol / DGBE | Chemical structure | H00 |
| CAS.No. | 112-34-5 | | |
| EINECS No. | 203-961-6 | | |
| Molecular weight | 162.23 | | |
| | | | |

| Physical properties | |
|---|--|
| Appearance | Colorless transparent liquid |
| Density,20℃,g/cm3 | 0.967 |
| Boiling point, $^\circ\!\!\!\mathrm{C}$ | 231 |
| Melting point, $^\circ\!\mathrm{C}$ | -68 |
| Flash point, $^{\circ}\!\!\mathbb{C}$ | 100 |
| Refractive index | 1.432 |
| Solubility | Soluble in water, ethanol, ether, oil and a variety of organic solvents. |
| | |

| Specification | | |
|--|------------------------------|--|
| Items | Enterprise Standard | |
| Appearance | Colorless transparent liquid | |
| Assay, % | ≥ 99.0 | |
| Moisture, % | ≤ 0.10 | |
| Acidity (HAC), % | ≤ 0.01 | |
| Color (Pt-Co) | \leq 15 | |
| Distillation Range, $^\circ\!\mathrm{C}$ | 227.0-235.0 | |
| | | |

Application

1) Because of its high boiling point, low volatility, can be used as paint, ink, resin and other solvents, soluble oils, dyes, resins, nitrocellulose, etc., also used for organic synthesis.

2) Mainly used in solvents, for coatings, dyes, resins, etc., also used as plasticizer intermediates and hydraulic brake liquid thinner, in addition to the production of piperonyl butoxide compounds.

 3) Mainly used as paint, printing ink, stamp printing ink, oil, resin and other solvents, can also be used as metal detergents, paint remover, de-lubricating oil, car engine detergent, dry cleaning solvent, epoxy resin, Pharmaceutical extractants; stabilizers for latex paints, evaporative inhibitors for aircraft coatings, surface processing improvers for high temperature baking enamels
4) Nitrocellulose, varnish, printing ink, oil, resin and other solvents. Plastic intermediates

Package

200kg iron drum, 16mt per 20"container



Safety on transportation

It belongs to common goods, always refer to MSDS.

Storage and handling

Keep tightly closed, store in a cool dry place. Please refer to the Materials Safety Data Sheet (MSDS) for the handling methods.

The information above is believed to be accurate and represents the best information currently available to us. However, In no event shall we be liable for any claims, losses, or damages of any third party resulting from its use. **Issue Date**: 1st, 12, 2016